



Vehicle model	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG
Year	(09/2021>)	(09/2021>)
Engine Type	F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)	F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500
N. of cylinders/cm3	4 / 2.998	4 / 2.998
Volts	12	12
Air Conditioning	Vehicles with or without A/C	Vehicles with or without A/C
Recommended fittings	Suction	Discharge
		
Compressors type	TM 16 UP-UPF 170	TM 21 / QP21
	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Vehicles 136hp, 160hp, 180hp with Hi-Matic 8-speed automatic gearbox, order P/N 1150008086 - On vehicles with Automatic Transmission Hi-Matic, recommended to use crankshaft pulley locking tool P/N 1149000398 	<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Vehicles 136hp, 160hp, 180hp with Hi-Matic 8-speed automatic gearbox, order P/N 1150008086 - On vehicles with Automatic Transmission Hi-Matic, recommended to use crankshaft pulley locking tool P/N 1149000398
Clutch type	Without clutch pulley	Without clutch pulley
	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø137 3.960 rpm
Kit No.	KB17118085	KB17118086
Last update	2022-07-15	2022-07-15

Vehicle model	DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 35 to 70 / S16-C16 35 to 70 / S18-C18 35 to 70 / S21-C21 35 to 70 / S14-C14 - CNG		DAILY 3.0 A50C18 / A65C18 / A70C18 A50C21 / A65C21 / A70C21		DAILY 3.0 A50C18 / A65C18 / A70C18 A50C21 / A65C21 / A70C21		
Year	(09/2021>)		(09/2021>)		(09/2019>)		(09/2019>)		
Engine Type	F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)		F1CFL (Euro 6d-full / Euro VI-E) F1CFA401C (CNG)		F1CFL411F*A (Euro VID) F1CFL4115 (Euro VID)		F1CFL411F*A (Euro VID) F1CFL4115 (Euro VID)		
CV(kW) @ rpm	160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		160 (118) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500 136 (100) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500		
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998		4 / 2.998		
Volts	12		12		12		12		
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	
Compressors type	TM 16 UP-UPF 170		TM 21 / QP21		TM 16 UP-UPF 170		TM 16 UP-UPF 170		
Comments	<ul style="list-style-type: none"> - "E"=TM-UNICLA; - UNICLA: Clutch drive plate Ø120 not suitable. - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		<ul style="list-style-type: none"> - "E"=TM-UNICLA; - UNICLA: Clutch drive plate Ø120 not suitable. - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		<ul style="list-style-type: none"> - Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398 		
Clutch type	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley	With clutch pulley	Without clutch pulley		
	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø137 3.960 rpm	Poly-V 8K Ø137 3.960 rpm	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø119 4.560 rpm	Poly-V 8K Ø119 4.560 rpm		
Kit No.	KB15018069		KB15018069E		KB15018069		KB15018069E		KB17118085
Last update	2022-07-15		2022-07-15		2021-12-13		2023-02-23		

Vehicle model	DAILY 3.0 A50C18 / A65C18 / A70C18 A50C21 / A65C21 / A70C21		DAILY 3.0 A50C18 / A65C18 / A70C18 A50C21 / A65C21 / A70C21		DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17		DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17		DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17		DAILY 3.0 A50C17 / A50C17P / A65C17 / A65C17P 70C17	
Year	(09/2019>)		(09/2019>)		(01/2012)		(01/2012)		(01/2012)		(01/2012)	
Engine Type	F1CFL411F*A (Euro VID) F1CFL4115 (Euro VID)		F1CFL411F*A (Euro VID) F1CFL4115 (Euro VID)		F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)		F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)		F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)		F1CE3481K (Euro 5) F1CFL411H*C (Euro 5b+) F1CFL411F*A (Euro 6)	
CV(kW) @ rpm	170 (125) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500 210 (154) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500		170 (125) @ 3.500 180 (132) @ 3.500	
N. of cylinders/cm3	4 / 2.998		4 / 2.998		4 / 2.998		4 / 2.998		4 / 2.998		4 / 2.998	
Volts	12		12		12		12		12		12	
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C	
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge	Suction	Discharge
Compressors type	TM 21 / QP21		TM 21 / QP21		TM 16 UP-UPF 170		TM 16 UP-UPF 170		TM 21 / QP21		TM 21 / QP21	
Comments	- Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398		- "E"=TM-UNICLA; - UNICLA: Clutch drive plate Ø 120 not suitable. - Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398		- Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398		- Can be fit in right hand drive vehicles - THE ORIGINAL ACCESSORIES BELT IS KEPT - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398		- Can be fit in right hand drive vehicles - Suitable for vehicles with 8-Speed Automatic Transmission Hi-Matic. Use crankshaft pulley locking tool P/N 1149000398	
Clutch type	Without clutch pulley		Without clutch pulley		Without clutch pulley		Without clutch pulley		Without clutch pulley		Without clutch pulley	
	Poly-V 8K Ø137 3.960 rpm		Poly-V 8K Ø137 3.960 rpm		Poly-V 8K Ø137 3.960 rpm		Poly-V 8K Ø119 4.560 rpm		Poly-V 8K Ø119 4.560 rpm		Poly-V 8K Ø137 3.960 rpm	
Kit No.	KB17118086		KB15028070 KB15028070E		KB15018069 KB15018069E		KB17118085		KB17118086		KB15028070 KB15028070E	
Last update	2019-10-10		2021-12-13		2021-09-23		2018-08-10		2018-08-10		2021-09-23	

Vehicle model	EuroCargo Tector 7 4X4 ML110E22 / ML110E25 / ML150E25 / ML150E28		EuroCargo		EuroMidi CC100E22FP		EuroMidi CC100E22FP		EuroMidi CC100E22FP			
Year	(2014>)		(2014>)		(2010<01/2020)		(02/2020>)		(2010>)			
Engine Type	F4AFE611A°C (Euro 6) F4AFE611E°C (Euro 6) F4AFE611C°C (Euro 6)		F4AFE611A°C (Euro 6) F4AFE611E°C (Euro 6) F4AFE611C°C (Euro 6) F4AFE611D°C (Euro 6)		F4AE3681B (Euro 4-5) F4AFE611A°C (Euro 6)		F4AFE611A°C (Euro 6)		F4AE3681B (Euro 4-5) F4AFE611A°C (Euro 6)			
CV(kW) @ rpm	220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500		220 (162) @ 2.500 250 (184) @ 2.500 280 (206) @ 2.500 320 (235) @ 2.500		217 (159) @ 2.700 220 (162) @ 2.700		217 (159) @ 2.700		217 (159) @ 2.700 220 (162) @ 2.700			
N. of cylinders/cm3	6 / 6.728		6 / 6.700		6 / 5.880 6 / 6.728		6 / 6.728		6 / 5.880 6 / 6.728			
Volts	24		24		24		24		24			
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C			
Recommended fittings	Suction		Discharge		Suction		Discharge		Suction		Discharge	
Compressors type			TM 31		TM 31		TM 31		TM 31			
Comments	<ul style="list-style-type: none"> - Can't be fit in right hand drive vehicles. - Compatible with ZF automatic gearbox - NOT COMPATIBLE with ALLISON automatic gearbox 		<ul style="list-style-type: none"> - Can't be fit in right hand drive vehicles. - No suitable for 220HP engine with automatic gear box. 		<ul style="list-style-type: none"> - Compressor fittings not supplied in the kit 		<ul style="list-style-type: none"> - Compressor fittings not supplied in the kit 		<ul style="list-style-type: none"> - Compressor fittings not supplied in the kit - Suitable for front box AC 			
Clutch type	Without clutch pulley		Without clutch pulley		Without clutch pulley		Without clutch pulley		Without clutch pulley			
	2B Ø158 2.975 rpm		2B Ø158 2.975 rpm		2B Ø158 3.400 rpm		2B Ø158 3.400 rpm		2B Ø158 3.400 rpm			
Kit No.	KB23108115		KB13038048		KB15068075		KB20028097		KB16048081			
Last update	2023-10-24		2014-03-28		2015-06-17		2020-03-06		2016-04-29			

Vehicle model	EuroMidi CC150E25FP		EuroMidi CC150E25FP		EuroMidi CC150E25FP				
Year	(2010>)		(2010>)		(2010>)				
Engine Type	F4AE3681D (Euro 4-5) F4AFE611E*C (Euro 6)		F4AE3681D (Euro 4-5) F4AFE611E*C (Euro 6)		F4AE3681D (Euro 4-5) F4AFE611E*C (Euro 6)				
CV(kW) @ rpm	251 (184) @ 2.700		251 (184) @ 2.700		251 (184) @ 2.700				
N. of cylinders/cm3	6 / 5.880 6 / 6.728		6 / 5.880 6 / 6.728		6 / 5.880 6 / 6.728				
Volts	24		24		24				
Air Conditioning	Vehicles with or without A/C		Vehicles with or without A/C		Vehicles with or without A/C				
Recommended fittings	Suction	Discharge	Suction	Discharge	Suction	Discharge			
Compressors type	TM 31		TM 31		TM 31				
Comments	- Compressor fittings not supplied in the kit		- Compressor fittings not supplied in the kit - Suitable for front box AC		- Compressor fittings not supplied in the kit - Suitable for front box AC - COMPATIBLE with automatic gearbox ALLISON				
Clutch type	Without clutch pulley		Without clutch pulley		Without clutch pulley				
	2B Ø158 3.400 rpm		2B Ø158 3.400 rpm		2B Ø158 3.400 rpm				
Kit No.	KB11018024		KB21098106		KB21108107				
Last update	2015-06-17		2021-09-28		2021-11-19				